

EX-918XXA series


Intel® Atom™ N2600 1.6GHz Fanless HMI



Features:

- Variety of LCD Panel Size Selections
- Flat Front Panel with IP65 Design
- Solid Aluminum Die-casting Chass
- Dual Core Low Power Fanless Sys





TOPSCCC TECHNOLOGY CO., LTD.

Specifications:

	EX-91807A	EX-91808A	EX-91812A	EX-91815A
System				
Processor	Intel® Atom™ N2600 Dual core 1.6GHz processor			
System Memory	On Board 2GB DDR3 memory			
System Chipset	Intel NM10			
External I/O Port	2 x USB 2.0 ports 2 x RJ-45 GbE ports 1 x DB-9 RS-232/422/485 COM1, Default RS-232 1 x DB-9 RS-232 Com2 1 x Audio Line-out 1 x HDMI port (Optional) 1 x 3-pin Terminal Block DC power input	2 x USB 2.0 ports 2 x RJ-45 GbE ports 1 x DB-9 RS-232/422/485 COM1, Default RS-232 1 x DB-9 RS-232 Com2 2 x DB-9 RS-422/485 Option 1 x Audio Line-out 1 x HDMI port (Optional) 1 x 3-pin Terminal Block DC power input		
Storage	1 x Half Size of 1.8" SATA HDD 1 x SD slot	1 x 2.5" SATA HDD 1 x SD slot		
Expansion Slots	1 x Internal Mini PCIe slot for Wfi or GSM/GPRS/3G module			
OS Support	Windows Embedded Standard 7, XP professional, XP Embedded, Embedded CE6.0			
Display				
Display Type	7" TFT-LCD	8" TFT-LCD	12.1" TFT-LCD	15" TFT-LCD
Max. Resolution	800x480	800x600	800x600	1024x768
Max. Color	262K	16.2M	16.2M	16.2M
Luminance (cd/m)	350	350	330	400
View Angle	140°/110°	140°/125°	160°/140°	160°/145°
Touch Screen				
Type	Resistive Touch, Projected Capacitive Touch (Optional)			
Light Transmission	80%, 90% (Optional)			
Power Supply				
Power Input	9~36V DC			
Mechanical				
Construction	Aluminum front bazel and chassis			
IP Rating	IP65 compliant front panel			
Mounting	Panel/VESA 75x75 Mount			
Dimension (WxHxD) (mm)	200x146x39	231x176x50	317x243x53	410x310x53
Net Weight (Kg)	2.3Kg	3.2Kg	4.0Kg	6.3Kg
Environmetal				
Operating Temperature (°C)	0~50			
Storage Temperature (°C)	-20~60			
Storage Humidity	10~90%@40°C, non-condensing			
CertifiCATE	CE/FCC ClassA			

TOPSCCC TECHNOLOGY CO., LTD.

5F., NO.12, Alley 345, Yang-Guang St. • 114 Nei-Hu, Taipei • Taiwan (R.O.C.)
 Tel.: +886-2-27999080 • Fax.: +886-2-26585042 • E-Mail: topsccc@topsccc.com
<http://www.topsccc.com> • <http://www.topsccc.com.tw> • <http://www.topsccc.co.th>